














WERKZEUGE AUS KERAMIK

antistatisch – antimagnetisch - Material: Zirkonoxid

1-750  Keramik-Abgleichschraubendreher-
satz 13-teilig in Scharnierdeckel-Box

Inhalt: beidseitiges Wechselheft 1-735 und 12 Keramik-Bits, Gewicht: 90 g

Nr.	Klingenlänge mm	Schneiden	mm	Gewicht g
1-751	32		0,90 x 0,30	1
1-752	32		1,30 x 0,30	1
1-753	32		1,50 x 0,30	1
1-754	32		1,80 x 0,30	1
1-755	32		1,95 x 0,35	1
1-756	32		2,50 x 0,70	1
1-757	32		3,00 x 0,30	1
1-761	32		1,95 SW	1
1-762	32		2,45 SW	1
1-765	32		KS Gr. 00	1
1-766	32		KS Gr. 0	1
1-767	32		2,40 x 0,80	1






















Abgleichschraubendreher und Bits

Klingen aus Keramik Schraubendreher mit leitfähigem Heft Nr.: 1-851 – 1-876

Bits Nr.: 1-751 – 1-776 zur Verwendung mit Wechselheft Nr.: 1-735



Nr.	Länge mm	Bit Nr.	Länge mm	Schneiden	mm	Gewicht g
1-851	110	1-751	32		0,90 x 0,30	10 / 1
1-852	110	1-752	32		1,30 x 0,30	10 / 1
1-853	110	1-753	32		1,50 x 0,30	10 / 1
1-854	110	1-754	32		1,80 x 0,30	10 / 1
1-855	110	1-755	32		1,95 x 0,35	10 / 1
1-856	110	1-756	32		2,50 x 0,70	10 / 1
1-857	110	1-757	32		3,00 x 0,30	10 / 1
1-858	110	1-758	32		3,00 x 0,70	10 / 1
1-861	110	1-761	32		1,95 SW	10 / 1
1-862	110	1-762	32		2,45 SW	10 / 1
1-863	110	1-763	32		2,60 SW	10 / 1
1-864	110	1-764	32		KS Gr. 000	10 / 1
1-865	110	1-765	32		KS Gr. 00	10 / 1
1-866	110	1-766	32		KS Gr. 0	10 / 1
1-867	110	1-767	32		2,40 x 0,80	10 / 1
1-873	110	1-773	32		0,70 x 1,40	10 / 1
1-874	110	1-774	32		3,00 x 1,00	10 / 1
1-875	110	1-775	32		1,20 x 1,20	10 / 1
1-876	110	1-776	32		1,30 x 0,40	10 / 1

