


ESD SMD tweezers ULTRA FINE 110 mm form PSF stainless steel, thin straight-pointed, dissipative

Art.-No.	5-078-UF-13
Description	ESD SMD tweezers ULTRA FINE 110 mm form PSF stainless steel, thin straight-pointed, dissipative
Application	Electronics, SMD/THT assembly, precision mechanics, robotics, watchmakers, jewelers, medical technology, precision work
Specification	not serrated jaws, tip tolerance +/-0.05
Material	stainless steel
Surface/Coating	ESD powder coated
Features	stainless, antimagnetic, acid-resistant, dissipative
Surface resistance	10^6 to 10^9 Ohm
Shape	NG: Normal tips straight
Icon No.	NG1

Dimensions and weight

A = 50 mm
B = 1 mm
C = 0.2 mm



length 130 mm
weight 20 g

Application and technical data

For precise gripping, holding, and positioning work in laboratories, on testing equipment, especially under the microscope. With a tip dimension of 0.2 mm with a tolerance of +/-0.05, also suitable for equipping robotics (pick-and-place), allows repeatable adjustment.

100% stainless steel anti-magnetic, rust and acid resistant, non-reflective matt fine polished. Stainless austenitic chromium nickel quality steel with low carbon content, for good corrosion resistance (not seawater resistant). Dissipative black ESD coating achieves a surface leakage resistance of 10^6 to 10^9 ohm.