



ESD bit box 45 pcs 4mm bits 5/32 inch + ESD handle + extension

Item No.

6-350


3 bit bars equipped with 36 special bits and 1 bit bar with 6 nut setter

Specification

precision repair kit for smartphones (I-Phone, Samsung, HTC) tablets and PCs 4 bit bars 4mm (5/32 inch) hex bits blade length 22 mm blade Ø 8 mm including ESD handle (dissipative 10^6 to 10^9 ohm) including bit extension 115 mm + 1/4 inch adapter for 4 mm bits quality steel sandblasted and nickel-plated 52-54 HRC dimensions box inside 130x80x14, outside 135x85x20 mm weight 215 g



6-350 ESD Bit-Box 45 tlg 6-350 ESD bit box 45 pcs													
	s-Reparaturset für Smartp repair kit for smartphones, ta				und	PCs							Ē
6-340-1	ESD Bithalter/ bit holder				þe	-	-	-			_	0	4 m 5/3
4-564	Bitadapter/bit adapter	6,35 1/4"	•	_	-	_					_	0	4 m 5/3
6-340-2	Bitverlängerung/ bit extension	4 ma 5/32		_	_	_	_	-	_	-	_	0	4 m 5/3
6-340-3	ESD Bit-Satz/ ESD Bit Set 42 tlg/42 pcs	4.mm 5/32		-	-	-			4.n 5/2	am 12*	•	- 1	_
		28 30 0 0	3.5 O	0 45	5.0 O	11	1	19 10	•	- 14	20	22.2	÷
	80 81 03 69 13 1	0 20 10	30	2 2	12	12.3	5 2.0	25	10 0	0.00	2	1.1	14



Application and technology

45-piece precision repair set consisting of a 115 mm bit extension, the 42-piece bit set with a conductive ESD handle made of aluminum with rotating cap and the 1/4 inch to 4 mm bit adapter.

In conjunction with the ESD handle suitable for all work on electrostatically sensitive components. Precision repair kit for Smartphones (I-Phone, Samsung, HTC). 3 bit bars equipped with 36 special security bits with C4 holder, 1 bit bar with 6 nut setter with C4 holder, quality steel sandblasted and nickel-plated, hardness 52-54 HRC, material plastic bar PP. Handle with slim and ergonomically shaped, surface resistance 10⁶ - 10⁹ ohm, Standards: IEC 61340-5-1. The rotatable centering head guarantees precision.

ESD screwdriver bit set consists of: 6-340-3 C4 Bit set 42 pcs, consists of: Slot 1.0-1.5-2.0-2.5-3.0 Cross-recess PH000-PH00-PH0-PH1 Torx T3-T4-T5-T6-T7-T8-T9-T10-T15 Hex 0.9-1.3-1.5-2.0-2.5-3.0 Wrench 2.5-3.0-3.5-4.0-4.5-5.0 Triangle 1.6-2.0-2.2-2.3, Square S0-S1 Pentalobe P2-P5-P6, SIM-Eject, Tri-Point 0-1 6-340-2 bit extension for 4 mm (5/32 inch) hex bits 6-340-1 ESD bit holder dissipative for 4 mm (5/32 inch) hex bits 4-564 bit adapter 1/4 inch to 4 mm bits, length 42.5 mm in V_KB_130x80x14_ESD plastic hinged lid box