

protective jaws for velcro aluminium with rubber 50 mm (pair)

Art.-No.**9-900-K50-ALG****Description**

protective jaws for velcro aluminium with rubber 50 mm (pair)

Features

Quick-change vice jaws suitable for vice jaws 9-205-K with jaw width 50 mm

flexible snap lock, connection to be removed again

solid, firm, stable and precise connection

for clamping parts with scratch-sensitive surfaces

ALUMINUM = non-magnetic light metal

RUBBER = elastic, water and oil resistant, resilient


Packing unit pair

extra parts article: KLETT-K050×25

Dual Lock snap fastener, self-adhesive 50×25 mm (PU10)

approx dimensions 50 × 30 × 14 mm

weight 72 g

**Application and technical data**

PRESSURE LOCK = over 1,000 locking cycles, material polyolefin, color black, adhesive acrylate (VHB), temperature resistance continuously -30 to +70°C (short term + 95°C), food-resistant, moisture-resistant, UV-resistant, aging-resistant, chemical and plasticizer-resistant, dynamic tensile strength approx. 21 N/cm², maximum static tensile strength and shear strength approx. 160 g/cm², flammability test passed according to FAR 25,853 (b-2). Storage unprocessed 12 months shelf life at 20°C storage temperature and 50% relative humidity. Dual Lock (ISO 9002 certified) is a patented pressure lock system from 3M.

Parts list